

View Online at <https://aerobasegroup.com/nsn/5925-01-367-9847>

**Body Length:**

2.490 inches

**Body Width:**

2.265 inches

**Case Material:**

Plastic

**Center To Center Distance Between Terminals Parallel To Length:**

1.940 inches

**Center To Center Distance Between Terminals Parallel To Width:**

0.750 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

2.060 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

0.750 inches

**Boss Height:**

0.140 inches

**Mounting Surface To Terminal End Distance:**

2.625 inches

**Pole Quantity:**

3

**Mounting Facility Type And Quantity:**

6 threaded hole

**Thready Qty Per Inch (tpi):**

32

**Maximum Continuous Load Current Rating Per Pole:**

10.0 amperes ac all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

250.0 ac all locations

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

1000.0 ac all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Magnetic all locations

**Trip Release Characteristic:**

Time delay all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

125.0 all locations

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

1 toggle

**Actuator Function:**

Trip-reset

**Actuator Position Designation:**

At each pole

**External Actuator Linkage Arrangement:**

One, two, and three linked

**Internal Trip Release Configuration:**

Series trip all locations

**Thread Size:**

0.138 inches

**Trip Delay Time In Seconds Per Rated Continuous Current:**

10.000 at 200 pct all locations and 100.000 at 200 pct all locations

**Frequency In Hertz:**

50.0 all locations or 60.0 all locations

**Thread Series Designator:**

Unc

**Terminal Type And Quantity:**

6 threaded stud

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A030a0