NSN 5925-01-369-8930

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-369-8930

| View Online at https://aerobasegroup.com/nsn/5925-01-369-8930 |
|--|
| Body Style: |
| Single pole type |
| Body Length: |
| 7.120 inches |
| Body Width: |
| 1.500 inches |
| Case Material: |
| Plastic |
| Center To Center Distance Between Terminals Parallel To Length: |
| 6.000 inches |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: |
| 2.781 inches |
| Boss Height: |
| 0.220 inches |
| Mounting Surface To Terminal End Distance: |
| 2.970 inches |
| Pole Quantity: |
| 1 |
| Mounting Facility Type And Quantity: |
| 2 threaded hole |
| Thready Qty Per Inch (tpi): |
| 32 |
| Maximum Continuous Load Current Rating Per Pole: |
| 250.0 amperes dc single location |
| Operating Voltage Type And Rating Per Pole In Volts: |
| 125.0 dc single location |
| Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: |
| 3500.0 dc single location |
| Circuit Protection Type: |
| Overcurrent single location |
| Trip Release Method: |
| Magnetic single location |
| Trip Release Characteristic: |
| Time delay single location |
| Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent: |
| 125.0 single location |
| Reset Method: |
| |
| Main Contact Tripping Mechanism Type: |
| Trip free |
| Request Reductor Turne And Quentity |
| Manual Actuator Type And Quantity: 1 toggle |

NSN 5925-01-369-8930

Circuit Breaker - Page 2 of 2



Actuator Function:

Trip-reset

Actuator Position Designation:

At pole one

Internal Trip Release Configuration:

Series trip single location

Thread Size:

0.138 inches

Trip Delay Time In Seconds Per Rated Continuous Current:

3.000 at 200 pct single location and 15.000 at 200 pct single location

Thread Series Designator:

Unc

Terminal Type And Quantity:

2 threaded stud

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A030a0