NSN 5925-01-370-0888



Circuit Breaker - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5925-01-370-0888 **Body Style:** Rectangular dimensional envelope **Overall Length:** 1.840 inches **Overall Height:** 0.400 inches **Overall Width:** 1.560 inches **Case Material:** Plastic **Pole Quantity: Mounting Facility Type And Quantity:** 2 clip **Maximum Continuous Load Current Rating Per Pole:** 5.0 amperes ac single location and 5.0 amperes dc single location Operating Voltage Type And Rating Per Pole In Volts: 120.0 ac single location and 32.0 dc single location **Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:** 2000.0 ac single location **Circuit Protection Type:** Overcurrent single location **Trip Release Method:** Magnetic single location **Trip Release Characteristic:** Time delay single location **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 125.0 single location **Reset Method:** Manual **Main Contact Tripping Mechanism Type: Manual Actuator Type And Quantity:** 1 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole one

Internal Trip Release Configuration:

Series trip single location

Trip Delay Time In Seconds Per Rated Continuous Current:

2.750 at 200 pct single location and 25.000 at 200 pct single location

NSN 5925-01-370-0888

Circuit Breaker - Page 2 of 2



	Freq	uency	In	Hertz	:
--	------	-------	----	-------	---

50.0 single location or 60.0 single location

Terminal Type And Quantity:

2 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A030a0