

View Online at <https://aerobasegroup.com/nsn/5925-01-370-3457>

Body Style:

Single pole type

Body Length:

2.000 inches

Body Width:

0.755 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

1.560 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.660 inches

Boss Height:

0.130 inches

Mounting Surface To Terminal End Distance:

2.032 inches

Pole Quantity:

1

Mounting Facility Type And Quantity:

2 threaded hole

Maximum Continuous Load Current Rating Per Pole:

30.0 amperes ac single location

Operating Voltage Type And Rating Per Pole In Volts:

115.0 ac single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

1000.0 ac single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Magnetic single location

Trip Release Characteristic:

Time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 single location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole one

Auxiliary Switch Function And Quantity:

1 alarm

Internal Trip Release Configuration:

Series trip single location

Thread Size:

0.138 inches

Trip Delay Time In Seconds Per Rated Continuous Current:

5.000 at 200 pct single location and 25.000 at 200 pct single location

Frequency In Hertz:

50.0 single location or 60.0 single location

Thread Series Designator:

Unc

Terminal Type And Quantity:

2 tab w/screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0