## NSN 5925-01-372-7137

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-372-7137 **Body Length:** 2.000 inches **Body Width:** 0.750 inches **Case Material:** Plastic Center To Center Distance Between Terminals Parallel To Length: 1.560 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 1.660 inches **Mounting Surface To Terminal End Distance:** 2.032 inches **Pole Quantity: Maximum Continuous Load Current Rating Per Pole:** 7.0 amperes dc single location Operating Voltage Type And Rating Per Pole In Volts: 50.0 dc single location **Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:** 2000.0 dc single location **Circuit Protection Type:** Overcurrent single location **Trip Release Method:** Magnetic single location **Trip Release Characteristic:** Time delay single location **Reset Method:** Manual **Main Contact Tripping Mechanism Type:** Trip free **Trip Delay Time In Seconds Per Rated Continuous Current:** 7.000 at 125 pct single location **Test Data Document:** 81349-mil-c-55629 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Specification Data:** 81349-mil-c-55629/7 government specification Shelf Life: N/a **Unit Of Measure:** 

No

**Demilitarization:** 

## NSN 5925-01-372-7137

Circuit Breaker - Page 2 of 2



Fiig:

A030a0