

View Online at <https://aerobasegroup.com/nsn/5925-01-373-2324>

Case Material:

Plastic

Pole Quantity:

2

Maximum Continuous Load Current Rating Per Pole:

10.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

240.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Magnetic all locations

Trip Release Characteristic:

Time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

Reset Method:

Manual

Trip Delay Time In Seconds Per Rated Continuous Current:

120.000 at 125 pct all locations

Frequency In Hertz:

60.0 all locations

Test Data Document:

81349-mil-c-55629 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

4 threaded stud

Specification Data:

81349-mil-c-55629/4 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0