NSN 5925-01-377-2285

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-377-2285

Body Style: Multipole-single actuator type **Body Length:** 2.500 inches **Body Width:** 1.500 inches **Case Material: Plastic Center To Center Distance Between Terminals Parallel To Length:** 1.938 inches **Center To Center Distance Between Terminals Parallel To Width:** 1.938 inches **Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:** 2.062 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.750 inches **End Application:** Panel, ac distb., p/n 2009-002-01 used onboard 47 ft mlb coast guard vessels **Boss Height:** 0.140 inches **Mounting Surface To Terminal End Distance:** 2.481 inches **Pole Quantity: Mounting Facility Type And Quantity:** 4 threaded hole Thready Qty Per Inch (tpi): 32 **Maximum Continuous Load Current Rating Per Pole:** 15.0 amperes ac all locations and 15.0 amperes dc all locations Operating Voltage Type And Rating Per Pole In Volts: 250.0 ac all locations and 65.0 dc all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 1000.0 ac all locations and 5000.0 dc all locations **Circuit Protection Type:** Overcurrent all locations **Trip Release Method:** Magnetic-hydraulic all locations **Trip Release Characteristic:** Instantaneous all locations **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

135.0 all locations

NSN 5925-01-377-2285

Circuit Breaker - Page 2 of 2



Reset Method:
Manual
Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
1 toggle
Actuator Function:
Reset
Internal Trip Release Configuration:
Series trip all locations
Thread Size:
0.138 inches
Frequency In Hertz:
60.0 all locations
Thread Series Designator:
Unc
Terminal Type And Quantity:
4 threaded stud
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A030a0