NSN 5925-01-381-5188

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-381-5188 **Body Style:** Multipole-single actuator type **Bushing Length:** Between 0.332 inches and 0.380 inches **Body Length:** 1.562 inches **Body Width:** 1.281 inches **Case Material:** Metal **Center To Center Distance Between Terminals Parallel To Length:** 0.906 inches **Center To Center Distance Between Terminals Parallel To Width:** Between 0.360 inches and 0.390 inches **Fragility Factor:** Moderately rugged **Mounting Surface To Terminal End Distance:** 1.828 inches **Pole Quantity: Mounting Facility Type And Quantity:** 1 threaded bushing w/panel seal Storage Type: General purpose warehouse **Special Handling Feature:** Magnetic **Features Provided:** High inrush protection Thready Qty Per Inch (tpi): 32 **Maximum Continuous Load Current Rating Per Pole:** 500.0 milliamperes ac second location **Operating Voltage Type And Rating Per Pole In Volts:** 250.0 ac all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 300.0 ac all locations **Circuit Protection Type:** Overcurrent all locations **Trip Release Method:**

Trip Release Characteristic: Time delay first location

Magnetic all locations

NSN 5925-01-381-5188 Circuit Breaker - Page 2 of 2



Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
135.0 all locations
Reset Method:
Manual
Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
1 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
Between pole one and two
Internal Trip Release Configuration:
Series trip all locations
Thread Size:
0.375 inches
Trip Delay Time In Seconds Per Rated Continuous Current:
0.055 at 200 pct first location and 0.950 at 200 pct first location
Inclosure Protection Type For Which Designed:
Hermetically sealed and vibration resistant and shock resistant and moisture resistant and corrosion resistant and fungus resistant
Frequency In Hertz:
50.0 first location or 60.0 first location
Unpackaged Unit Weight:
4.000 ounces
Thread Series Designator:
Unef
Terminal Type And Quantity:
4 wire hook
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Fiig:
A030a0