

View Online at <https://aerobasegroup.com/nsn/5925-01-382-1005>

Body Style:

Multipole-multiple actuator type

Body Length:

2.500 inches

Body Width:

1.500 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

1.938 inches

Center To Center Distance Between Terminals Parallel To Width:

0.750 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

2.062 inches

Switch Contact Arrangement:

Single pole, double throw

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.750 inches

Boss Height:

0.140 inches

Mounting Surface To Terminal End Distance:

2.860 inches

Pole Quantity:

2

Mounting Facility Type And Quantity:

4 threaded hole

Maximum Continuous Load Current Rating Per Pole:

15.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

265.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

1000.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Magnetic all locations

Trip Release Characteristic:

Time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

2 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole one

External Actuator Linkage Arrangement:

One and two linked

Auxiliary Switch Function And Quantity:

1 alarm

Internal Trip Release Configuration:

Series trip all locations

Thread Size:

0.138 inches

Switch Location And Position Designation:

Internal at pole one

Trip Delay Time In Seconds Per Rated Continuous Current:

9.500 at 200 pct all locations and 150.000 at 200 pct all locations

Switch Terminal Type:

Tab, solder lug

Switch Current Rating And Type In Amps:

10.0 ac and 3.0 dc

Switch Voltage Rating And Type In Volts:

250.0 ac and 50.0 dc

Frequency In Hertz:

440.0 all locations

Thread Series Designator:

Unc

Terminal Type And Quantity:

4 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0