

View Online at <https://aerobasegroup.com/nsn/5925-01-387-6502>

Body Style:

Multipole-single actuator type

Body Length:

11.000 inches

Body Width:

7.500 inches

Case Material:

Plastic

Mounting Surface To Terminal End Distance:

4.000 inches

Pole Quantity:

3

Mounting Facility Type And Quantity:

3 unthreaded hole and 3 terminal

Maximum Continuous Load Current Rating Per Pole:

350.0 amperes ac all locations and 350.0 amperes dc all locations

Operating Voltage Type And Rating Per Pole In Volts:

600.0 ac all locations and 500.0 dc all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

65000.0 ac all locations and 65000.0 dc all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Magnetic all locations

Trip Release Characteristic:

Instantaneous all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

138.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Internal Trip Release Configuration:

Series trip all locations

Frequency In Hertz:

60.0 all locations

Terminal Type And Quantity:

6 compression

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0