NSN 5925-01-392-6278



Circuit Breaker - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5925-01-392-6278 **Body Style:** Single pole type **Body Length:** 2.000 inches **Body Width:** 0.750 inches **Case Material:** Plastic **Center To Center Distance Between Terminals Parallel To Length:** 1.660 inches **Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:** 1.660 inches **Boss Height:** 0.130 inches **Mounting Surface To Terminal End Distance:** 2.000 inches **Pole Quantity: Mounting Facility Type And Quantity:** 2 threaded hole **Maximum Continuous Load Current Rating Per Pole:** 2.5 amperes dc single location **Operating Voltage Type And Rating Per Pole In Volts:** 65.0 dc single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 2000.0 dc single location **Circuit Protection Type:** Overcurrent single location **Trip Release Method:** Magnetic single location **Trip Release Characteristic:** Time delay single location **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 125.0 single location **Reset Method:** Manual **Main Contact Tripping Mechanism Type:** Trip free **Manual Actuator Type And Quantity:** 1 toggle

Actuator Function: Trip-reset

NSN 5925-01-392-6278

Circuit Breaker - Page 2 of 2



Internal Trip Release Configuration:
Series trip single location
Thread Size:
0.138 inches
Trip Delay Time In Seconds Per Rated Continuous Current:
0.032 at 200 pct single location
Thread Series Designator:
Unc
Terminal Type And Quantity:
2 knife blade
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A030a0