

View Online at <https://aerobasegroup.com/nsn/5925-01-393-0359>

Body Style:

Single pole type

Body Length:

2.490 inches

Body Width:

0.750 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

1.940 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

2.060 inches

Boss Height:

0.150 inches

Mounting Surface To Terminal End Distance:

2.625 inches

Pole Quantity:

1

Mounting Facility Type And Quantity:

2 threaded hole

Maximum Continuous Load Current Rating Per Pole:

10.0 amperes ac single location

Operating Voltage Type And Rating Per Pole In Volts:

250.0 ac single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

5000.0 ac single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Magnetic single location

Trip Release Characteristic:

Time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

138.0 single location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Internal Trip Release Configuration:

Series trip single location

Thread Size:

0.190 inches

Trip Delay Time In Seconds Per Rated Continuous Current:

0.200 at 200 pct single location and 2.000 at 200 pct single location

Frequency In Hertz:

400.0 single location

Thread Series Designator:

Unc

Terminal Type And Quantity:

2 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0