

View Online at <https://aerobasegroup.com/nsn/5925-01-394-4830>

**Body Style:**

Multipole-single actuator type

**Case Material:**

Plastic

**Pole Quantity:**

3

**Mounting Facility Type And Quantity:**

1 threaded bushing

**Thready Qty Per Inch (tpi):**

32

**Maximum Continuous Load Current Rating Per Pole:**

7.5 amperes ac all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

120.0 ac all locations

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

1000.0 ac all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Thermal all locations

**Trip Release Characteristic:**

Time delay all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

125.0 all locations

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Internal Trip Release Configuration:**

Series trip all locations

**Thread Size:**

0.469 inches

**Trip Delay Time In Seconds Per Rated Continuous Current:**

10.000 at 200 pct all locations and 70.000 at 200 pct all locations

**Special Features:**

Epoxy around terminals with eccobond 51 epoxy

**Frequency In Hertz:**

400.0 all locations

**Thread Series Designator:**

Un

**Terminal Type And Quantity:**

6 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0