

View Online at <https://aerobasegroup.com/nsn/5925-01-394-7251>

Body Style:

Multipole-multiple actuator type

Body Length:

2.500 inches

Body Width:

3.040 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

Between 1.655 inches and 1.695 inches

Center To Center Distance Between Terminals Parallel To Width:

0.750 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

2.060 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.750 inches

Boss Height:

0.138 inches

Mounting Surface To Terminal End Distance:

2.625 inches

Pole Quantity:

4

Mounting Facility Type And Quantity:

8 threaded hole

Maximum Continuous Load Current Rating Per Pole:

80.0 amperes ac second location

Operating Voltage Type And Rating Per Pole In Volts:

250.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

1000.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Magnetic all locations

Trip Release Characteristic:

Time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

138.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

4 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At each pole

Internal Trip Release Configuration:

Series trip third location

Thread Size:

0.138 inches

Trip Delay Time In Seconds Per Rated Continuous Current:

2.700 at 200 pct third location and 10.100 at 200 pct third location

Frequency In Hertz:

60.0 all locations

Thread Series Designator:

Unc

Terminal Type And Quantity:

10 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0