NSN 5925-01-394-8246

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-394-8246 **Body Style:** Single pole type **Bushing Length:** Between 0.332 inches and 0.380 inches **Body Length:** 1.562 inches **Body Width:** 0.625 inches **Case Material:** Metal **Center To Center Distance Between Terminals Parallel To Length:** 0.906 inches **Switch Contact Arrangement:** Single pole, double throw **Mounting Surface To Terminal End Distance:** 1.700 inches **Pole Quantity:** 1 **Mounting Facility Type And Quantity:** 1 threaded bushing w/panel seal **Maximum Continuous Load Current Rating Per Pole:** 15.0 amperes ac single location and 15.0 amperes dc single location **Operating Voltage Type And Rating Per Pole In Volts:** 240.0 ac single location and 50.0 dc single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 300.0 ac single location and 500.0 dc single location **Circuit Protection Type:** Overcurrent single location **Trip Release Method:** Magnetic single location **Trip Release Characteristic:** Time delay single location **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 125.0 single location **Reset Method:** Manual **Main Contact Tripping Mechanism Type:** Trip free **Manual Actuator Type And Quantity:** 1 toggle

Actuator Function:

Trip-reset

NSN 5925-01-394-8246 Circuit Breaker - Page 2 of 2



| Actuator Position Designation: |
|--|
| At pole one |
| Auxiliary Switch Function And Quantity: |
| 1 alarm |
| Internal Trip Release Configuration: |
| Series trip single location |
| Thread Size: |
| 0.375 inches |
| Switch Location And Position Designation: |
| Internal at pole one |
| Trip Delay Time In Seconds Per Rated Continuous Current: |
| 0.040 at 200 pct single location and 25.000 at 200 pct single location |
| Switch Terminal Type: |
| Pin |
| Switch Current Rating And Type In Amps: |
| 0.5 ac and 0.5 dc |
| Switch Voltage Rating And Type In Volts: |
| 120.0 ac and 50.0 dc |
| Frequency In Hertz: |
| 47.5 single location or 63.0 single location |
| Thread Series Designator: |
| Unef |
| Terminal Type And Quantity: |
| 2 wire hook |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A030a0 |
| |
| |
| |