

View Online at <https://aerobasegroup.com/nsn/5925-01-395-1526>

Body Style:

Single pole type

Body Length:

1.610 inches

Body Width:

0.695 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

1.250 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.610 inches

Boss Height:

0.125 inches

Mounting Surface To Terminal End Distance:

1.770 inches

Pole Quantity:

1

Mounting Facility Type And Quantity:

2 clip

Maximum Continuous Load Current Rating Per Pole:

0.250 amperes ac single location

Operating Voltage Type And Rating Per Pole In Volts:

250.0 ac single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

1000.0 ac single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Magnetic single location

Trip Release Characteristic:

Time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 single location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole one

Internal Trip Release Configuration:

Series trip single location

Trip Delay Time In Seconds Per Rated Continuous Current:

0.050 at 200 pct single location and 0.950 at 200 pct single location

Special Features:

Illuminated handle

Frequency In Hertz:

60.0 single location

Terminal Type And Quantity:

2 knife blade

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0