

View Online at <https://aerobasegroup.com/nsn/5925-01-397-6450>

Body Style:

Multipole-single actuator type

Body Length:

1.560 inches

Body Width:

Between 1.365 inches and 1.385 inches

Body Height:

1.460 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

Between 1.095 inches and 1.155 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

Between 0.962 inches and 0.982 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.250 inches

Boss Height:

Between 0.083 inches and 0.103 inches

Pole Quantity:

2

Mounting Facility Type And Quantity:

2 clip

Maximum Continuous Load Current Rating Per Pole:

5.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

250.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

45.000 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Magnetic all locations

Trip Release Characteristic:

Time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

135.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

Between pole one and two

Internal Trip Release Configuration:

Series trip all locations

Trip Delay Time In Seconds Per Rated Continuous Current:

0.100 at 200 pct all locations and 2.000 at 200 pct all locations

Inclosure Protection Type For Which Designed:

General purpose

Frequency In Hertz:

50.0 all locations or 60.0 all locations

Terminal Type And Quantity:

4 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0