

View Online at <https://aerobasegroup.com/nsn/5925-01-397-6450>

**Body Style:**

Multipole-single actuator type

**Body Length:**

1.560 inches

**Body Width:**

Between 1.365 inches and 1.385 inches

**Body Height:**

1.460 inches

**Case Material:**

Plastic

**Center To Center Distance Between Terminals Parallel To Length:**

Between 1.095 inches and 1.155 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

Between 0.962 inches and 0.982 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

0.250 inches

**Boss Height:**

Between 0.083 inches and 0.103 inches

**Pole Quantity:**

2

**Mounting Facility Type And Quantity:**

2 clip

**Maximum Continuous Load Current Rating Per Pole:**

5.0 amperes ac all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

250.0 ac all locations

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

45.000 ac all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Magnetic all locations

**Trip Release Characteristic:**

Time delay all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

135.0 all locations

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

1 toggle

**Actuator Function:**

Trip-reset

**Actuator Position Designation:**

Between pole one and two

**Internal Trip Release Configuration:**

Series trip all locations

**Trip Delay Time In Seconds Per Rated Continuous Current:**

0.100 at 200 pct all locations and 2.000 at 200 pct all locations

**Inclosure Protection Type For Which Designed:**

General purpose

**Frequency In Hertz:**

50.0 all locations or 60.0 all locations

**Terminal Type And Quantity:**

4 pin

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A030a0