NSN 5925-01-406-3474



Circuit Breaker - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5925-01-406-3474 **Body Style:** Rectangular dimensional envelope **Overall Length:** 2.000 inches **Overall Height:** 1.500 inches **Overall Width:** 1.860 inches **Case Material:** Plastic **Pole Quantity: Mounting Facility Type And Quantity:** 4 threaded hole **Maximum Continuous Load Current Rating Per Pole:** 10.0 amperes ac all locations **Operating Voltage Type And Rating Per Pole In Volts:** 120.0 ac all locations **Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:** 1000.0 ac all locations **Circuit Protection Type:** Overcurrent all locations **Trip Release Method:** Magnetic all locations **Trip Release Characteristic:** Time delay all locations **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 125.0 all locations **Reset Method:** Manual **Main Contact Tripping Mechanism Type: Manual Actuator Type And Quantity:** 1 toggle **Actuator Function:** Trip-reset **Actuator Position Designation:** At pole one **Internal Trip Release Configuration:** Series trip all locations

Thread Size:

0.138 inches

NSN 5925-01-406-3474

Circuit Breaker - Page 2 of 2



Trip Delay Time In Seconds Per Rated Continuous Current:

2.000 at 200 pct all locations and 20.000 at 200 pct all locations

Frequency In Hertz:

60.0 all locations

Thread Series Designator:

Unc

Terminal Type And Quantity:

6 tab w/screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0