

View Online at <https://aerobasegroup.com/nsn/5925-01-411-9726>

**Body Style:**

Single pole type

**Bushing Length:**

0.380 inches

**Body Length:**

1.700 inches

**Body Width:**

1.562 inches

**Center To Center Distance Between Terminals Parallel To Length:**

0.906 inches

**Pole Quantity:**

1

**Maximum Continuous Load Current Rating Per Pole:**

12.5 amperes ac single location

**Operating Voltage Type And Rating Per Pole In Volts:**

240.0 ac single location and 50.0 dc single location

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

300.0 ac single location and 500.0 dc single location

**Circuit Protection Type:**

Overcurrent single location

**Trip Release Method:**

Magnetic single location

**Trip Release Characteristic:**

Time delay single location

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

200.0 single location

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Internal Trip Release Configuration:**

Series trip single location

**Trip Delay Time In Seconds Per Rated Continuous Current:**

0.500 at 200 pct single location and 9.000 at 200 pct single location

**Frequency In Hertz:**

400.0 single location

**Special Test Features:**

81349-m39019/01-252s

**Test Data Document:**

81349-mil-c-39019c specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Specification Data:**

81349-mil-c-39019c government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0