

View Online at <https://aerobasegroup.com/nsn/5925-01-413-5389>

Body Style:

Single pole type

Body Length:

2.500 inches

Body Width:

0.750 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

1.938 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

2.062 inches

End Application:

An/fsq-151

Boss Height:

0.140 inches

Mounting Surface To Terminal End Distance:

2.860 inches

Pole Quantity:

1

Mounting Facility Type And Quantity:

Clip

Maximum Continuous Load Current Rating Per Pole:

20.0 amperes ac single location

Operating Voltage Type And Rating Per Pole In Volts:

250.0 ac single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

1000.0 ac single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Magnetic-hydraulic single location

Trip Release Characteristic:

Time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 single location

Ultimate Trip Time Per Pole In Seconds:

10.000 single location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

2 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole one

Internal Trip Release Configuration:

Relay trip single location

Trip Release Duty Cycle:

Continuous single location

Trip Delay Time In Seconds Per Rated Continuous Current:

1.100 at 200 pct single location and 0.100 at 600 pct single location and 0.004 at 1000 pct single location

Trip Release Ambient Temperature Rating:

-40.0 degrees celsius single location and 85.0 degrees celsius single location

Frequency In Hertz:

400.0 single location

Terminal Type And Quantity:

2 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0