

View Online at <https://aerobasegroup.com/nsn/5925-01-413-5389>

**Body Style:**

Single pole type

**Body Length:**

2.500 inches

**Body Width:**

0.750 inches

**Case Material:**

Plastic

**Center To Center Distance Between Terminals Parallel To Length:**

1.938 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

2.062 inches

**End Application:**

An/fsq-151

**Boss Height:**

0.140 inches

**Mounting Surface To Terminal End Distance:**

2.860 inches

**Pole Quantity:**

1

**Mounting Facility Type And Quantity:**

Clip

**Maximum Continuous Load Current Rating Per Pole:**

20.0 amperes ac single location

**Operating Voltage Type And Rating Per Pole In Volts:**

250.0 ac single location

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

1000.0 ac single location

**Circuit Protection Type:**

Overcurrent single location

**Trip Release Method:**

Magnetic-hydraulic single location

**Trip Release Characteristic:**

Time delay single location

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

125.0 single location

**Ultimate Trip Time Per Pole In Seconds:**

10.000 single location

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

2 toggle

**Actuator Function:**

Trip-reset

**Actuator Position Designation:**

At pole one

**Internal Trip Release Configuration:**

Relay trip single location

**Trip Release Duty Cycle:**

Continuous single location

**Trip Delay Time In Seconds Per Rated Continuous Current:**

1.100 at 200 pct single location and 0.100 at 600 pct single location and 0.004 at 1000 pct single location

**Trip Release Ambient Temperature Rating:**

-40.0 degrees celsius single location and 85.0 degrees celsius single location

**Frequency In Hertz:**

400.0 single location

**Terminal Type And Quantity:**

2 threaded stud

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0