

View Online at <https://aerobasegroup.com/nsn/5925-01-414-4678>

**Body Style:**

Single pole type

**Bushing Length:**

0.625 inches

**Body Length:**

0.750 inches

**Body Width:**

2.000 inches

**Case Material:**

Metal

**Center To Center Distance Between Terminals Parallel To Length:**

1.530 inches

**Switch Contact Arrangement:**

Single pole, double throw

**Mounting Surface To Terminal End Distance:**

2.232 inches

**Pole Quantity:**

1

**Mounting Facility Type And Quantity:**

1 threaded bushing w/panel seal

**Thready Qty Per Inch (tpi):**

32

**Maximum Continuous Load Current Rating Per Pole:**

3.0 amperes dc single location

**Operating Voltage Type And Rating Per Pole In Volts:**

50.0 dc single location

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

2000.0 dc single location

**Circuit Protection Type:**

Overcurrent single location

**Trip Release Method:**

Magnetic single location

**Trip Release Characteristic:**

Time delay single location

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

150.0 single location

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

1 toggle

**Actuator Function:**

Trip-reset

**Actuator Position Designation:**

At pole one

**Auxiliary Switch Function And Quantity:**

Alarm

**Internal Trip Release Configuration:**

Series trip single location

**Thread Size:**

0.500 inches

**Switch Location And Position Designation:**

Internal at pole one

**Trip Delay Time In Seconds Per Rated Continuous Current:**

2.600 at 200 pct single location and 20.000 at 200 pct single location

**Inclosure Protection Type For Which Designed:**

Fungus resistant

**Switch Terminal Type:**

Screw

**Switch Current Rating And Type In Amps:**

1.0 dc

**Switch Voltage Rating And Type In Volts:**

50.0 dc

**Test Data Document:**

81349-mil-c-55629 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Un

**Terminal Type And Quantity:**

2 tab w/screw

**Specification Data:**

81349-mil-c-55629/20 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A030a0