

View Online at <https://aerobasegroup.com/nsn/5925-01-417-4628>

**Case Material:**

Plastic

**End Application:**

Switchboard, thruster; p/n 213041-m3 onboard wlb 225 ft coast guard vessels

**Pole Quantity:**

3

**Maximum Continuous Load Current Rating Per Pole:**

800.0 amperes ac all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

600.0 ac all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Magnetic all locations

**Trip Release Characteristic:**

Time delay all locations

**Reset Method:**

Electric

**Main Contact Tripping Mechanism Type:**

Nontrip free

**Internal Trip Release Configuration:**

Series/relay trip all locations

**Trip Release Duty Cycle:**

Continuous all locations

**Reset Actuator Voltage Rating And Type In Volts:**

120.0 ac

**Special Features:**

Air arc circuit breaker; 6 normally open; 6 normally closed; isolated auxiliaries

**Frequency In Hertz:**

60.0 all locations

**Terminal Type And Quantity:**

6 bus bar

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0