

View Online at <https://aerobasegroup.com/nsn/5925-01-420-9432>

Body Style:

Rectangular dimensional envelope

Overall Length:

1.750 inches

Overall Height:

0.750 inches

Overall Width:

0.406 inches

Case Material:

Plastic

Pole Quantity:

1

Mounting Facility Type And Quantity:

1 terminal

Maximum Continuous Load Current Rating Per Pole:

5.0 amperes ac single location

Operating Voltage Type And Rating Per Pole In Volts:

250.0 ac single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

1000.0 ac single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Magnetic-hydraulic single location

Trip Release Characteristic:

Time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 single location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 push button

Actuator Function:

Reset

Actuator Position Designation:

At pole one

Internal Trip Release Configuration:

Series trip single location

Inclosure Protection Type For Which Designed:

General purpose

Frequency In Hertz:

50.0 single location or 60.0 single location

Terminal Type And Quantity:

2 eyelet

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0