NSN 5925-01-422-6653

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-422-6653

Overall Length:
4.260 inches
Overall Height:
Between 3.390 inches and 3.450 inches
Overall Width:
2.250 inches
Case Material:
Plastic
Pole Quantity:
1
Mounting Facility Type And Quantity:
2 threaded hole
Maximum Continuous Load Current Rating Per Pole:
5.0 amperes ac all locations and 5.0 amperes dc all locations
Operating Voltage Type And Rating Per Pole In Volts:
115.0 ac all locations and 28.0 dc all locations
Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:
3600.0 ac all locations and 3600.0 dc all locations
Circuit Protection Type:
Overcurrent all locations
Trip Release Method:
Thermal all locations
Trip Release Characteristic:
Time delay all locations
Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
125.0 all locations
Reset Method:
Manual
Main Contact Tripping Mechanism Type:
Trip free
Internal Trip Release Configuration:
Series trip all locations
Trip Delay Time In Seconds Per Rated Continuous Current:
7.000 at 200 pct all locations and 40.000 at 200 pct all locations
Inclosure Protection Type For Which Designed:
General purpose
Trip Release Ambient Tempurature Rating:
40.0 degrees celsius all locations
Frequency In Hertz:
400.0 all locations
Terminal Type And Quantity:

2 threaded stud

NSN 5925-01-422-6653

Circuit Breaker - Page 2 of 2



_					
٠.	n	_	I+	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0