

View Online at <https://aerobasegroup.com/nsn/5925-01-423-2764>

Pole Quantity:

1

Maximum Continuous Load Current Rating Per Pole:

3.0 amperes ac single location

Operating Voltage Type And Rating Per Pole In Volts:

240.0 ac single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

1000.0 ac single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Magnetic single location

Trip Release Characteristic:

Time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

135.0 single location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 push-pull

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole one

Internal Trip Release Configuration:

Series trip single location

Trip Delay Time In Seconds Per Rated Continuous Current:

0.100 at 200 pct single location and 2.000 at 200 pct single location

Frequency In Hertz:

50.0 single location or 60.0 single location

Terminal Type And Quantity:

2 eyelet

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0