

View Online at <https://aerobasegroup.com/nsn/5925-01-425-4332>

Body Style:

Multipole-multiple actuator type

Body Length:

2.000 inches

Body Width:

1.500 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

1.560 inches

Center To Center Distance Between Terminals Parallel To Width:

0.750 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.660 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.750 inches

Boss Height:

0.130 inches

Mounting Surface To Terminal End Distance:

1.950 inches

Pole Quantity:

2

Mounting Facility Type And Quantity:

4 clip

Maximum Continuous Load Current Rating Per Pole:

10.0 amperes ac second location and 10.0 amperes dc second location

Operating Voltage Type And Rating Per Pole In Volts:

240.0 ac first location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

2000.0 ac second location and 1000.0 dc second location

Circuit Protection Type:

Overcurrent second location

Trip Release Method:

Magnetic second location

Auxiliary Trip Coil Voltage Type And Rating In Volts:

115.0 ac second location

Trip Release Characteristic:

Time delay first location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

150.0 second location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

2 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At each pole

Internal Trip Release Configuration:

Series trip w/remote trip feature second location

Trip Release Duty Cycle:

Continuous second location

Trip Delay Time In Seconds Per Rated Continuous Current:

0.400 at 150 pct second location and 6.000 at 150 pct second location

Frequency In Hertz:

50.0 second location or 60.0 second location or 400.0 second location

Terminal Type And Quantity:

5 knife blade

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0