

View Online at <https://aerobasegroup.com/nsn/5925-01-425-8687>

**Body Style:**

Multipole-multiple actuator type

**Body Length:**

5.800 inches

**Body Width:**

3.108 inches

**Case Material:**

Plastic

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

2.750 inches

**Boss Height:**

0.220 inches

**Mounting Surface To Terminal End Distance:**

2.610 inches

**Pole Quantity:**

3

**Mounting Facility Type And Quantity:**

6 threaded hole

**Maximum Continuous Load Current Rating Per Pole:**

40.0 amperes ac all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

240.0 ac all locations

**Trip Release Method:**

Magnetic all locations

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**External Actuator Linkage Arrangement:**

One, two, and three linked

**Internal Trip Release Configuration:**

Series trip all locations

**Criticality Code Justification:**

Feat

**Special Features:**

Weapon system essential; magnetic, unsealed, trip free, three pole, back mounted; altered item from mil-c-55629/18 circuit breaker, part number m55629/18knknkn; pressure solderless connector terminals which accomodate no. 14 awg through no 1 awg copper wire; calibrated for mounting in a horizontal plane with operating lever pivot up (table mount); temperature operating limits -40 degrees f to 185 degrees f; weight 2 lbs

**Frequency In Hertz:**

50.0 all locations or 50.0 all locations

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A030a0