

View Online at <https://aerobasegroup.com/nsn/5925-01-431-3138>

**Body Style:**

Single pole type

**Body Length:**

2.000 inches

**Body Width:**

1.813 inches

**Body Height:**

1.875 inches

**Case Material:**

Plastic

**Center To Center Distance Between Terminals Parallel To Length:**

0.625 inches

**Unthreaded Mounting Hole Diameter:**

0.174 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

Between 1.566 inches and 1.582 inches

**Fragility Factor:**

Moderately rugged

**Pole Quantity:**

1

**Mounting Facility Type And Quantity:**

2 unthreaded hole

**Storage Type:**

General purpose warehouse

**Maximum Continuous Load Current Rating Per Pole:**

25.0 amperes dc single location

**Operating Voltage Type And Rating Per Pole In Volts:**

30.0 dc single location

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

575.0 dc single location

**Circuit Protection Type:**

Overcurrent single location

**Trip Release Method:**

Thermal single location

**Trip Release Characteristic:**

Time delay single location

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

138.0 single location

**Reset Method:**

Automatic

**Internal Trip Release Configuration:**

Series trip single location

**Trip Delay Time In Seconds Per Rated Continuous Current:**

8.000 at 200 pct single location and 50.000 at 200 pct single location

**Inclosure Protection Type For Which Designed:**

Waterproof and vibration resistant and shock resistant and salt spray proof and fungus resistant

**Trip Release Ambient Temperature Rating:**

25.0 degrees celsius single location

**Unpackaged Unit Weight:**

2.250 ounces

**Terminal Type And Quantity:**

2 quick disconnect, female

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A030a0