## NSN 5925-01-431-7055



Circuit Breaker - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5925-01-431-7055 **Body Style:** Single pole type **Body Length:** 2.000 inches **Body Width:** 0.750 inches **Case Material:** Metal **Center To Center Distance Between Terminals Parallel To Length:** 1.530 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 0.657 inches **Mounting Surface To Terminal End Distance:** 2.200 inches **Pole Quantity: Mounting Facility Type And Quantity:** 3 threaded stud **Maximum Continuous Load Current Rating Per Pole:** 30.0 amperes ac single location **Operating Voltage Type And Rating Per Pole In Volts:** 115.0 ac single location **Circuit Protection Type:** Error voltage single location **Trip Release Method:** Solid state single location **Auxiliary Trip Coil Voltage Type And Rating In Volts:** 100.0 ac single location **Trip Release Characteristic:** Instantaneous single location **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 61.0 single location **Reset Method:** Manual **Main Contact Tripping Mechanism Type:** Nontrip free **Thread Size:** 0.138 inches **Trip Release Duty Cycle:** Continuous single location

Feat

**Criticality Code Justification:** 

## NSN 5925-01-431-7055

Circuit Breaker - Page 2 of 2



Special Features:
Weapon system essential
Frequency In Hertz:
60.0 single location
Thread Series Designator:
Unc
Terminal Type And Quantity:
4 tab w/screw
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

**Fiig:** A030a0