

View Online at <https://aerobasegroup.com/nsn/5925-01-432-0547>

Body Style:

Single pole type

Body Length:

2.000 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

1.660 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.660 inches

End Application:

Automated surface observing system (asos)

Mounting Surface To Terminal End Distance:

1.930 inches

Pole Quantity:

1

Mounting Facility Type And Quantity:

2 threaded hole

Maximum Continuous Load Current Rating Per Pole:

0.50 amperes ac single location

Operating Voltage Type And Rating Per Pole In Volts:

250.0 ac single location and 50.0 dc single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

1000.0 ac single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Magnetic single location

Trip Release Characteristic:

Time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 single location

Frequency In Hertz:

50.0 single location or 60.0 single location

Terminal Type And Quantity:

2 tab w/screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0