

View Online at <https://aerobasegroup.com/nsn/5925-01-432-5167>

**Body Style:**

Single pole type

**Bushing Length:**

0.359 inches

**Body Length:**

0.780 inches

**Body Width:**

0.580 inches

**Case Material:**

Metal

**Center To Center Distance Between Terminals Parallel To Length:**

0.593 inches

**Mounting Surface To Terminal End Distance:**

1.420 inches

**Pole Quantity:**

1

**Mounting Facility Type And Quantity:**

1 threaded bushing

**Maximum Continuous Load Current Rating Per Pole:**

500.0 milliamperes ac single location and 500.0 milliamperes dc single location

**Operating Voltage Type And Rating Per Pole In Volts:**

115.0 ac single location and 28.0 dc single location

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

100.0 ac single location and 100.0 dc single location

**Circuit Protection Type:**

Overcurrent single location

**Trip Release Method:**

Thermal single location

**Trip Release Characteristic:**

Time delay single location

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

145.0 single location

**Reset Method:**

Manual

**Internal Trip Release Configuration:**

Series trip single location

**Trip Delay Time In Seconds Per Rated Continuous Current:**

2.000 at 200 pct single location and 20.000 at 200 pct single location

**Trip Release Ambient Temperature Rating:**

25.0 degrees celsius single location

**Terminal Type And Quantity:**

2 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0