NSN 5925-01-435-9492

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-435-9492

view Online at https://aerobasegroup.com/nsii/3923-01-433-9492
Body Style:
Single pole type
Body Length:
2.000 inches
Body Width:
0.750 inches
Case Material:
Plastic
Center To Center Distance Between Terminals Parallel To Length:
1.530 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
1.660 inches
Boss Height:
0.130 inches
Mounting Surface To Terminal End Distance:
1.890 inches
Pole Quantity:
1
Mounting Facility Type And Quantity:
2 threaded hole
Thready Qty Per Inch (tpi):
32
32
32 Maximum Continuous Load Current Rating Per Pole:
32 Maximum Continuous Load Current Rating Per Pole: 25.0 amperes ac single location
32 Maximum Continuous Load Current Rating Per Pole: 25.0 amperes ac single location Operating Voltage Type And Rating Per Pole In Volts:
 32 Maximum Continuous Load Current Rating Per Pole: 25.0 amperes ac single location Operating Voltage Type And Rating Per Pole In Volts: 250.0 ac single location
 32 Maximum Continuous Load Current Rating Per Pole: 25.0 amperes ac single location Operating Voltage Type And Rating Per Pole In Volts: 250.0 ac single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:
 32 Maximum Continuous Load Current Rating Per Pole: 25.0 amperes ac single location Operating Voltage Type And Rating Per Pole In Volts: 250.0 ac single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 277.0 ac single location
 32 Maximum Continuous Load Current Rating Per Pole: 25.0 amperes ac single location Operating Voltage Type And Rating Per Pole In Volts: 250.0 ac single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 277.0 ac single location Circuit Protection Type:
 32 Maximum Continuous Load Current Rating Per Pole: 25.0 amperes ac single location Operating Voltage Type And Rating Per Pole In Volts: 250.0 ac single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 277.0 ac single location Circuit Protection Type: Overcurrent single location
 32 Maximum Continuous Load Current Rating Per Pole: 25.0 amperes ac single location Operating Voltage Type And Rating Per Pole In Volts: 250.0 ac single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 277.0 ac single location Circuit Protection Type: Overcurrent single location Trip Release Method:
 32 Maximum Continuous Load Current Rating Per Pole: 25.0 amperes ac single location Operating Voltage Type And Rating Per Pole In Volts: 250.0 ac single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 277.0 ac single location Circuit Protection Type: Overcurrent single location Trip Release Method: Magnetic-hydraulic single location
 32 Maximum Continuous Load Current Rating Per Pole: 25.0 amperes ac single location Operating Voltage Type And Rating Per Pole In Volts: 250.0 ac single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 277.0 ac single location Circuit Protection Type: Overcurrent single location Trip Release Method: Magnetic-hydraulic single location Trip Release Characteristic:
 32 Maximum Continuous Load Current Rating Per Pole: 25.0 amperes ac single location Operating Voltage Type And Rating Per Pole In Volts: 250.0 ac single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 277.0 ac single location Circuit Protection Type: Overcurrent single location Trip Release Method: Magnetic-hydraulic single location Trip Release Characteristic: Instantaneous single location
 32 Maximum Continuous Load Current Rating Per Pole: 25.0 amperes ac single location Operating Voltage Type And Rating Per Pole In Volts: 250.0 ac single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 277.0 ac single location Circuit Protection Type: Overcurrent single location Trip Release Method: Magnetic-hydraulic single location Trip Release Characteristic: Instantaneous single location Utimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
32 Maximum Continuous Load Current Rating Per Pole: 25.0 amperes ac single location Operating Voltage Type And Rating Per Pole In Volts: 250.0 ac single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 277.0 ac single location Circuit Protection Type: Overcurrent single location Trip Release Method: Magnetic-hydraulic single location Trip Release Characteristic: Instantaneous single location Utimate Trip Rating Of Continuous Current Rating Per Pole In Percent: 125.0 single location
 32 Maximum Continuous Load Current Rating Per Pole: 25.0 amperes ac single location Operating Voltage Type And Rating Per Pole In Volts: 250.0 ac single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 277.0 ac single location Circuit Protection Type: Overcurrent single location Trip Release Method: Instantaneous single location Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent: 125.0 single location Reset Method:
32 Maximum Continuous Load Current Rating Per Pole: 25.0 amperes ac single location Operating Voltage Type And Rating Per Pole In Volts: 250.0 ac single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 277.0 ac single location Circuit Protection Type: Overcurrent single location Trip Release Method: Magnetic-hydraulic single location Trip Release Characteristic: Instantaneous single location Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent: 125.0 single location Reset Method: Manual

Series trip single location

NSN 5925-01-435-9492

Circuit Breaker - Page 2 of 2



Thread Size:

0.138 inches

Frequency In Hertz:

50.0 single location or 60.0 single location

Thread Series Designator:

Unc

Terminal Type And Quantity:

2 quick disconnect, male

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A030a0