

View Online at <https://aerobasegroup.com/nsn/5925-01-436-2462>

**Body Style:**

Multipole-multiple actuator type

**Body Length:**

5.125 inches

**Body Width:**

3.108 inches

**Case Material:**

Plastic

**Center To Center Distance Between Terminals Parallel To Length:**

3.547 inches

**Center To Center Distance Between Terminals Parallel To Width:**

1.026 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

2.750 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

1.026 inches

**Boss Height:**

0.220 inches

**Mounting Surface To Terminal End Distance:**

3.520 inches

**Pole Quantity:**

3

**Mounting Facility Type And Quantity:**

6 threaded hole

**Maximum Continuous Load Current Rating Per Pole:**

25.0 amperes ac all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

240.0 ac all locations

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

5000.0 ac all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Magnetic all locations

**Trip Release Characteristic:**

Time delay all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

125.0 all locations

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

3 toggle

**Actuator Function:**

Trip-reset

**Actuator Position Designation:**

At each pole

**External Actuator Linkage Arrangement:**

One, two, and three linked

**Internal Trip Release Configuration:**

Series trip all locations

**Thread Size:**

0.138 inches

**Trip Delay Time In Seconds Per Rated Continuous Current:**

2.100 at 200 pct all locations and 10.500 at 200 pct all locations

**Frequency In Hertz:**

60.0 all locations

**Test Data Document:**

81349-mil-c-55629 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Unc

**Terminal Type And Quantity:**

6 threaded stud

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0