

View Online at <https://aerobasegroup.com/nsn/5925-01-437-9172>

Body Style:

Multipole-multiple actuator type

Body Length:

1.562 inches

Body Width:

1.281 inches

Center To Center Distance Between Terminals Parallel To Length:

0.906 inches

Center To Center Distance Between Terminals Parallel To Width:

0.625 inches

Unthreaded Mounting Hole Diameter:

0.250 inches

End Application:

F15s lantirn

Pole Quantity:

2

Mounting Facility Type And Quantity:

2 threaded bushing w/panel seal

Operating Voltage Type And Rating Per Pole In Volts:

240.0 ac all locations and 50.0 dc all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Magnetic all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

Between pole one and two

Switch Location And Position Designation:

External between pole one and two

Frequency In Hertz:

60.0 all locations or 400.0 all locations

Thread Series Designator:

Unc

Terminal Type And Quantity:

4 tab w/screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0

Mil-std (military Standard):

Mil-prf-39019 spec.