

View Online at <https://aerobasegroup.com/nsn/5925-01-440-6388>

**Body Style:**

Multipole-single actuator type

**Body Length:**

4.125 inches

**Body Width:**

3.344 inches

**Body Height:**

3.375 inches

**Case Material:**

Plastic

**Center To Center Distance Between Terminals Parallel To Length:**

2.625 inches

**Center To Center Distance Between Terminals Parallel To Width:**

1.125 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

0.500 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

2.938 inches

**Boss Height:**

0.125 inches

**Pole Quantity:**

3

**Mounting Facility Type And Quantity:**

2 threaded hole

**Thready Qty Per Inch (tpi):**

24

**Maximum Continuous Load Current Rating Per Pole:**

25.0 amperes ac all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

500.0 ac all locations

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

5000.0 ac all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Thermal all locations

**Trip Release Characteristic:**

Instantaneous all locations and time delay all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

115.0 all locations

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

1 toggle

**Actuator Function:**

Trip-reset

**Actuator Position Designation:**

At each pole

**Internal Trip Release Configuration:**

Series trip all locations

**Thread Size:**

0.216 inches

**Trip Delay Time In Seconds Per Rated Continuous Current:**

10.000 at 200 pct all locations and 200.000 at 200 pct all locations

**Trip Release Ambient Temperature Rating:**

50.0 degrees celsius all locations

**Frequency In Hertz:**

400.0 all locations

**Thread Series Designator:**

Unc

**Terminal Type And Quantity:**

6 quick disconnect, female

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0