

View Online at <https://aerobasegroup.com/nsn/5925-01-441-8987>

Body Style:

Multipole-single actuator type

Bushing Length:

0.250 inches

Body Length:

1.312 inches

Body Width:

2.160 inches

Body Height:

2.170 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

0.750 inches

Center To Center Distance Between Terminals Parallel To Width:

0.688 inches

Pole Quantity:

3

Mounting Facility Type And Quantity:

1 threaded bushing

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

35.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

120.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

1000.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Thermal all locations

Trip Release Characteristic:

Time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

138.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Internal Trip Release Configuration:

Series trip all locations

Thread Size:

0.469 inches

Trip Delay Time In Seconds Per Rated Continuous Current:

10.000 at 200 pct all locations and 70.000 at 200 pct all locations

Trip Release Ambient Temperature Rating:

25.0 degrees celsius all locations

Frequency In Hertz:

400.0 all locations

Thread Series Designator:

Uns

Terminal Type And Quantity:

6 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0