

View Online at <https://aerobasegroup.com/nsn/5925-01-441-9569>

**Body Style:**

Multipole-single actuator type

**Bushing Length:**

0.625 inches

**Body Length:**

2.000 inches

**Body Width:**

2.265 inches

**Case Material:**

Metal

**Center To Center Distance Between Terminals Parallel To Length:**

1.530 inches

**Center To Center Distance Between Terminals Parallel To Width:**

0.750 inches

**Switch Contact Arrangement:**

Double pole, single throw, normally open

**End Application:**

F15i lantern

**Mounting Surface To Terminal End Distance:**

2.232 inches

**Pole Quantity:**

3

**Mounting Facility Type And Quantity:**

Threaded bushing w/panel seal

**Maximum Continuous Load Current Rating Per Pole:**

30.0 amperes ac all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

115.0 ac all locations

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

2000.0 ac all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Magnetic all locations

**Auxiliary Trip Coil Voltage Type And Rating In Volts:**

10.0 ac third location

**Trip Release Characteristic:**

Time delay all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

150.0 all locations

**Ultimate Trip Time Per Pole In Seconds:**

0.500 all locations

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

1 toggle

**Actuator Function:**

Trip-reset

**Actuator Position Designation:**

At pole two

**Auxiliary Switch Function And Quantity:**

Alarm

**Internal Trip Release Configuration:**

Series trip w/dual rating first location

**Thread Size:**

32.000 inches

**Trip Release Duty Cycle:**

Continuous all locations

**Switch Location And Position Designation:**

Internal at pole three

**Trip Delay Time In Seconds Per Rated Continuous Current:**

0.500 at 150 pct all locations

**Trip Release Ambient Temperature Rating:**

-40.0 degrees celsius all locations and 85.0 degrees celsius all locations

**Thread Tolerance Class:**

2b external

**Frequency In Hertz:**

400.0 all locations

**Thread Series Designator:**

Unef

**Terminal Type And Quantity:**

Quick disconnect, male

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A030a0