

View Online at <https://aerobasegroup.com/nsn/5925-01-444-3856>

Body Style:

Single pole type

Body Length:

1.950 inches

Body Width:

1.250 inches

Case Material:

Metal

Center To Center Distance Between Terminals Parallel To Length:

0.875 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

0.000 inches

End Application:

F-15i lantirn

Mounting Surface To Terminal End Distance:

1.780 inches

Pole Quantity:

2

Mounting Facility Type And Quantity:

1 threaded bushing w/panel seal and 2 threaded hole

Maximum Continuous Load Current Rating Per Pole:

15.0 amperes ac single location

Operating Voltage Type And Rating Per Pole In Volts:

120.0 ac single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

150.0 ac single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Magnetic single location

Trip Release Characteristic:

Time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

18.7 single location

Ultimate Trip Time Per Pole In Seconds:

5.000 single location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Internal Trip Release Configuration:

Series trip single location

Thread Size:

0.138 inches and 0.375 inches

Trip Delay Time In Seconds Per Rated Continuous Current:

0.000 at 125 pct single location

Frequency In Hertz:

50.0 single location or 60.0 single location

Thread Series Designator:

Unef and unf

Terminal Type And Quantity:

4 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0