

View Online at <https://aerobasegroup.com/nsn/5925-01-446-0642>

Body Style:

Single pole type

Overall Length:

1.968 inches

Overall Width:

0.074 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

1.606 inches

Unthreaded Mounting Hole Diameter:

0.492 millimeters

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

0.000 inches

Switch Contact Arrangement:

Single pole, single throw, normally open

End Application:

F-15i lantrin

Boss Height:

0.059 inches

Mounting Surface To Terminal End Distance:

2.656 inches

Pole Quantity:

1

Mounting Facility Type And Quantity:

1 unthreaded hole

Maximum Continuous Load Current Rating Per Pole:

1.5 amperes ac single location

Operating Voltage Type And Rating Per Pole In Volts:

250.0 ac single location and 65.0 dc single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

1000.0 ac single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Magnetic-hydraulic single location

Trip Release Characteristic:

Instantaneous single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

1.5 single location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

Push-pull

Actuator Function:

Trip-reset

Auxiliary Switch Function And Quantity:

Alarm

Internal Trip Release Configuration:

Series trip w/auxiliary load terminal single location

Switch Location And Position Designation:

External at pole one

Switch Terminal Type:

Knife blade

Switch Current Rating And Type In Amps:

1.0 ac

Switch Voltage Rating And Type In Volts:

250.0 ac

Thread Tolerance Class:

External

Special Features:

Metric bushing mount 12 mm

Frequency In Hertz:

50.0 single location or 60.0 single location

Terminal Type And Quantity:

Knife blade

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0