

View Online at <https://aerobasegroup.com/nsn/5925-01-446-4792>

**Body Style:**

Single pole type

**Bushing Length:**

0.400 inches

**Body Length:**

1.375 inches

**Body Width:**

0.680 inches

**Case Material:**

Plastic

**Center To Center Distance Between Terminals Parallel To Length:**

1.125 inches

**Switch Contact Arrangement:**

Single pole, single throw, normally closed

**End Application:**

F-15i lantern

**Mounting Surface To Terminal End Distance:**

1.960 inches

**Pole Quantity:**

1

**Mounting Facility Type And Quantity:**

Threaded bushing

**Thready Qty Per Inch (tpi):**

32

**Maximum Continuous Load Current Rating Per Pole:**

0.75 amperes ac single location

**Operating Voltage Type And Rating Per Pole In Volts:**

250.0 ac single location and 50.0 dc single location

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

6.75 ac single location

**Circuit Protection Type:**

Overcurrent single location

**Trip Release Method:**

Magnetic single location

**Trip Release Characteristic:**

Time delay single location

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

135.0 single location

**Ultimate Trip Time Per Pole In Seconds:**

7.000 single location

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

1 push-pull

**Actuator Function:**

Trip-reset

**Actuator Position Designation:**

At pole one

**Auxiliary Switch Function And Quantity:**

1 alarm

**Internal Trip Release Configuration:**

Series trip single location

**Thread Size:**

0.375 inches

**Switch Location And Position Designation:**

External at pole one

**Trip Delay Time In Seconds Per Rated Continuous Current:**

0.300 at 135 pct single location and 7.000 at 135 pct single location

**Switch Terminal Type:**

Knife blade

**Switch Current Rating And Type In Amps:**

0.1 ac

**Switch Voltage Rating And Type In Volts:**

32.0 ac and 32.0 dc

**Frequency In Hertz:**

50.0 single location or 60.0 single location

**Thread Series Designator:**

Unef

**Terminal Type And Quantity:**

2 tab w/screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0