

View Online at <https://aerobasegroup.com/nsn/5925-01-452-4490>

**Body Style:**

Rectangular dimensional envelope

**Overall Length:**

2.000 inches

**Overall Height:**

1.515 inches

**Overall Width:**

1.640 inches

**Case Material:**

Plastic

**Pole Quantity:**

2

**Mounting Facility Type And Quantity:**

4 threaded hole

**Maximum Continuous Load Current Rating Per Pole:**

7.5 amperes ac all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

277.0 ac all locations and 65.0 dc all locations

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

5000.0 ac all locations and 1000.0 dc all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Magnetic all locations

**Trip Release Characteristic:**

Time delay all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

125.0 all locations

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Actuator Function:**

Trip-reset

**Actuator Position Designation:**

At pole two

**Internal Trip Release Configuration:**

Series trip all locations

**Thread Size:**

3.0 millimeters

**Thread Pitch In Millimeters:**

4.75

**Trip Delay Time In Seconds Per Rated Continuous Current:**

0.700 at 125 pct all locations and 12.000 at 125 pct all locations

**Special Features:**

Red with white marking rocker actuator

**Frequency In Hertz:**

50.0 all locations or 60.0 all locations

**Thread Series Designator:**

Iso m

**Terminal Type And Quantity:**

4 threaded stud

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0