## NSN 5925-01-452-9853

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-452-9853 **Body Style:** Multipole-single actuator type **Body Length:** 2.000 inches **Body Width:** 1.515 inches **Body Height:** 2.232 inches **Case Material: Plastic Center To Center Distance Between Terminals Parallel To Width:** 0.750 inches **Boss Height:** 0.625 inches **Pole Quantity: Mounting Facility Type And Quantity:** 4 threaded hole **Maximum Continuous Load Current Rating Per Pole:** 2.5 amperes dc all locations **Operating Voltage Type And Rating Per Pole In Volts:** 120.0 ac all locations **Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:** 3500.0 ac all locations **Circuit Protection Type:** Overvoltage all locations **Trip Release Method:** Magnetic all locations **Trip Release Characteristic:** Time delay all locations **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 150.0 all locations **Reset Method:** Manual **Main Contact Tripping Mechanism Type:** Trip free **Manual Actuator Type And Quantity:** 1 toggle **Actuator Function:** Trip-reset

**Actuator Position Designation:** 

At pole two

## NSN 5925-01-452-9853

Circuit Breaker - Page 2 of 2



Internal Trip Release Configuration:
Series trip all locations
Thread Size:
0.138 inches
Trip Delay Time In Seconds Per Rated Continuous Current:
125.000 at 200 pct all locations
Frequency In Hertz:
50.0 all locations or 60.0 all locations
Thread Series Designator:
Unc
Terminal Type And Quantity:
4 tab w/screw
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A030a0