## NSN 5925-01-454-8693

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-454-8693 **Body Length:** 1.562 inches **Body Width:** 1.937 inches **Case Material: Plastic** Center To Center Distance Between Terminals Parallel To Length: 0.623 inches **Center To Center Distance Between Terminals Parallel To Width:** 0.905 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: Between 1.364 inches and 1.424 inches **Mounting Surface To Terminal End Distance:** 1.950 inches **Pole Quantity: Mounting Facility Type And Quantity:** 2 threaded hole **Maximum Continuous Load Current Rating Per Pole:** 20.0 amperes dc all locations **Operating Voltage Type And Rating Per Pole In Volts:** 240.0 ac all locations and 50.0 dc all locations **Circuit Protection Type:** Overvoltage all locations **Trip Release Method:** Magnetic all locations **Auxiliary Trip Coil Voltage Type And Rating In Volts:** 240.0 ac all locations and 50.0 dc all locations **Trip Release Characteristic:** Time delay all locations **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 800.0 all locations **Reset Method:** Manual **Main Contact Tripping Mechanism Type:** Trip free **Internal Trip Release Configuration:** Series trip w/auxiliary load terminal and remote trip feature all locations **Thread Size:** 0.250 inches **Trip Release Duty Cycle:** 

Continuous all locations

## NSN 5925-01-454-8693

Circuit Breaker - Page 2 of 2



## **Trip Delay Time In Seconds Per Rated Continuous Current:**

0.060 at 800 pct all locations

Frequency In Hertz:

400.0 all locations

## **Test Data Document:**

81349-mil-prf-39019 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread	oenes	Desidi	IALUI.

Unc

**Terminal Type And Quantity:** 

6 tab w/screw

**Specification Data:** 

81349-mil-prf-39019/6 government specification

Shelf Life:

N/a

**Unit Of Measure:** 

--

**Demilitarization:** 

No

Fiig:

A030a0

Mil-std (military Standard):

Mil-prf-39019 spec.