

View Online at <https://aerobasegroup.com/nsn/5925-01-462-4648>

Body Style:

Single pole type

Bushing Length:

Between 0.458 inches and 0.478 inches

Body Length:

Between 1.365 inches and 1.385 inches

Body Width:

Between 0.670 inches and 0.690 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

Between 1.095 inches and 1.155 inches

Mounting Surface To Terminal End Distance:

Between 1.672 inches and 1.732 inches

Pole Quantity:

1

Mounting Facility Type And Quantity:

1 threaded bushing

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

1.5 amperes dc single location

Operating Voltage Type And Rating Per Pole In Volts:

32.0 dc single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

1000.0 dc single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Magnetic single location

Trip Release Characteristic:

Time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

135.0 single location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Internal Trip Release Configuration:

Series trip single location

Thread Size:

0.500 inches

Trip Delay Time In Seconds Per Rated Continuous Current:

0.300 at 135 pct single location and 7.000 at 135 pct single location

Special Features:

White paddle handle; 50/60 hz fast delay w/inertia wheel; black panel dress nut; locking ring

Thread Series Designator:

Un

Terminal Type And Quantity:

2 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0