

View Online at <https://aerobasegroup.com/nsn/5925-01-462-4648>

**Body Style:**

Single pole type

**Bushing Length:**

Between 0.458 inches and 0.478 inches

**Body Length:**

Between 1.365 inches and 1.385 inches

**Body Width:**

Between 0.670 inches and 0.690 inches

**Case Material:**

Plastic

**Center To Center Distance Between Terminals Parallel To Length:**

Between 1.095 inches and 1.155 inches

**Mounting Surface To Terminal End Distance:**

Between 1.672 inches and 1.732 inches

**Pole Quantity:**

1

**Mounting Facility Type And Quantity:**

1 threaded bushing

**Thready Qty Per Inch (tpi):**

32

**Maximum Continuous Load Current Rating Per Pole:**

1.5 amperes dc single location

**Operating Voltage Type And Rating Per Pole In Volts:**

32.0 dc single location

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

1000.0 dc single location

**Circuit Protection Type:**

Overcurrent single location

**Trip Release Method:**

Magnetic single location

**Trip Release Characteristic:**

Time delay single location

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

135.0 single location

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Internal Trip Release Configuration:**

Series trip single location

**Thread Size:**

0.500 inches

**Trip Delay Time In Seconds Per Rated Continuous Current:**

0.300 at 135 pct single location and 7.000 at 135 pct single location

**Special Features:**

White paddle handle; 50/60 hz fast delay w/inertia wheel; black panel dress nut; locking ring

**Thread Series Designator:**

Un

**Terminal Type And Quantity:**

2 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A030a0