# NSN 5925-01-462-4828

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-462-4828

view Online at https://aerobasegroup.com/nsn/5925-01-462-4828
Body Style:
Single pole type
Body Length:
5.125 inches
Body Width:
1.026 inches
Case Material:
Plastic
Center To Center Distance Between Terminals Parallel To Length:
3.550 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
2.750 inches
Boss Height:
0.220 inches
Mounting Surface To Terminal End Distance:
3.550 inches
Pole Quantity:
1
Mounting Facility Type And Quantity:
2 threaded hole
Thready Qty Per Inch (tpi):
Thready Qty Per Inch (tpi): 32
32
32 Maximum Continuous Load Current Rating Per Pole:
32 Maximum Continuous Load Current Rating Per Pole: 15.0 amperes ac single location
32 Maximum Continuous Load Current Rating Per Pole: 15.0 amperes ac single location Operating Voltage Type And Rating Per Pole In Volts:
<ul> <li>32</li> <li>Maximum Continuous Load Current Rating Per Pole:</li> <li>15.0 amperes ac single location</li> <li>Operating Voltage Type And Rating Per Pole In Volts:</li> <li>240.0 ac single location</li> </ul>
<ul> <li>32</li> <li>Maximum Continuous Load Current Rating Per Pole:</li> <li>15.0 amperes ac single location</li> <li>Operating Voltage Type And Rating Per Pole In Volts:</li> <li>240.0 ac single location</li> <li>Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:</li> </ul>
<ul> <li>32</li> <li>Maximum Continuous Load Current Rating Per Pole:</li> <li>15.0 amperes ac single location</li> <li>Operating Voltage Type And Rating Per Pole In Volts:</li> <li>240.0 ac single location</li> <li>Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:</li> <li>5000.0 ac single location</li> </ul>
<ul> <li>32</li> <li>Maximum Continuous Load Current Rating Per Pole:</li> <li>15.0 amperes ac single location</li> <li>Operating Voltage Type And Rating Per Pole In Volts:</li> <li>240.0 ac single location</li> <li>Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:</li> <li>5000.0 ac single location</li> <li>Circuit Protection Type:</li> </ul>
<ul> <li>32</li> <li>Maximum Continuous Load Current Rating Per Pole:</li> <li>15.0 amperes ac single location</li> <li>Operating Voltage Type And Rating Per Pole In Volts:</li> <li>240.0 ac single location</li> <li>Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:</li> <li>5000.0 ac single location</li> <li>Circuit Protection Type:</li> <li>Overcurrent single location</li> </ul>
<ul> <li>32</li> <li>Maximum Continuous Load Current Rating Per Pole:</li> <li>15.0 amperes ac single location</li> <li>Operating Voltage Type And Rating Per Pole In Volts:</li> <li>240.0 ac single location</li> <li>Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:</li> <li>5000.0 ac single location</li> <li>Circuit Protection Type:</li> <li>Overcurrent single location</li> <li>Trip Release Method:</li> </ul>
<ul> <li>32</li> <li>Maximum Continuous Load Current Rating Per Pole:</li> <li>15.0 amperes ac single location</li> <li>Operating Voltage Type And Rating Per Pole In Volts:</li> <li>240.0 ac single location</li> <li>Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:</li> <li>5000.0 ac single location</li> <li>Circuit Protection Type:</li> <li>Overcurrent single location</li> <li>Trip Release Method:</li> <li>Magnetic single location</li> </ul>
32 Maximum Continuous Load Current Rating Per Pole: 15.0 amperes ac single location Operating Voltage Type And Rating Per Pole In Volts: 240.0 ac single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 5000.0 ac single location Circuit Protection Type: Overcurrent single location Trip Release Method: Magnetic single location
32 Maximum Continuous Load Current Rating Per Pole: 15.0 amperes ac single location Operating Voltage Type And Rating Per Pole In Volts: 240.0 ac single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 5000.0 ac single location Circuit Protection Type: Overcurrent single location Trip Release Method: Magnetic single location Trip Release Characteristic: Time delay single location
<ul> <li>32</li> <li>Maximum Continuous Load Current Rating Per Pole:</li> <li>15.0 amperes ac single location</li> <li>Operating Voltage Type And Rating Per Pole In Volts:</li> <li>240.0 ac single location</li> <li>Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:</li> <li>5000.0 ac single location</li> <li>Circuit Protection Type:</li> <li>Overcurrent single location</li> <li>Trip Release Method:</li> <li>Magnetic single location</li> <li>Trip Release Characteristic:</li> <li>Time delay single location</li> <li>Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:</li> </ul>
32 Maximum Continuous Load Current Rating Per Pole: 15.0 amperes ac single location Operating Voltage Type And Rating Per Pole In Volts: 240.0 ac single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 5000.0 ac single location Circuit Protection Type: Overcurrent single location Trip Release Method: Magnetic single location Trip Release Characteristic: Time delay single location Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent: 125.0 single location
32 Maximum Continuous Load Current Rating Per Pole: 15.0 amperes ac single location Operating Voltage Type And Rating Per Pole In Volts: 240.0 ac single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 5000.0 ac single location Circuit Protection Type: Overcurrent single location Circuit Protection Type: Overcurrent single location Trip Release Method: Tip Release Characteristic: Time delay single location Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent: 125.0 single location Reset Method:
<ul> <li>32</li> <li>Maximum Continuous Load Current Rating Per Pole:</li> <li>15.0 amperes ac single location</li> <li>Operating Voltage Type And Rating Per Pole In Volts:</li> <li>240.0 ac single location</li> <li>Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:</li> <li>5000.0 ac single location</li> <li>Circuit Protection Type:</li> <li>Overcurrent single location</li> <li>Trip Release Method:</li> <li>Trip Release Characteristic:</li> <li>Time delay single location</li> <li>Utimate Trip Rating Of Continuous Current Rating Per Pole In Percent:</li> <li>125.0 single location</li> <li>Reset Method:</li> <li>Manual</li> </ul>

Series trip single location

# NSN 5925-01-462-4828

Circuit Breaker - Page 2 of 2



### Thread Size:

0.138 inches

#### Trip Delay Time In Seconds Per Rated Continuous Current:

12.000 at 125 pct single location and 80.000 at 125 pct single location

Inclosure Protection Type For Which Designed:

Fungus resistant and moisture resistant

### Frequency In Hertz:

50.0 single location or 60.0 single location

#### **Thread Series Designator:**

Unc

#### **Terminal Type And Quantity:**

2 threaded stud

Shelf Life:

N/a

#### Unit Of Measure:

---

## Demilitarization:

No

#### Fiig:

A030a0