## NSN 5925-01-462-4829



Circuit Breaker - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5925-01-462-4829 **Body Style:** Single pole type **Body Length:** 5.125 inches **Body Width:** 1.026 inches **Case Material: Plastic Center To Center Distance Between Terminals Parallel To Length:** 3.550 inches **Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:** 2.750 inches **Boss Height:** 0.220 inches **Mounting Surface To Terminal End Distance:** 3.550 inches **Pole Quantity:** 1 **Mounting Facility Type And Quantity:** 2 threaded hole Thready Qty Per Inch (tpi): 32 **Maximum Continuous Load Current Rating Per Pole:** 5.0 amperes ac single location Operating Voltage Type And Rating Per Pole In Volts: 240.0 ac single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 5000.0 ac single location **Circuit Protection Type:** Overcurrent single location **Trip Release Method:** Magnetic single location **Trip Release Characteristic:** Time delay single location **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 125.0 single location **Reset Method:** Manual **Main Contact Tripping Mechanism Type:** 

Trip free

**Internal Trip Release Configuration:** 

Series trip single location

## NSN 5925-01-462-4829

Circuit Breaker - Page 2 of 2

A030a0



Thread Size:
0.138 inches
Trip Delay Time In Seconds Per Rated Continuous Current:
12.000 at 125 pct single location and 80.000 at 125 pct single location
Inclosure Protection Type For Which Designed:
Fungus resistant and moisture resistant
Frequency In Hertz:
50.0 single location or 60.0 single location
Thread Series Designator:
Unc
Terminal Type And Quantity:
2 threaded stud
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Filg: