

View Online at <https://aerobasegroup.com/nsn/5925-01-462-5251>

Body Style:

Multipole-multiple actuator type

Body Length:

5.125 inches

Body Width:

3.108 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

3.550 inches

Center To Center Distance Between Terminals Parallel To Width:

1.026 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

2.750 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.026 inches

Boss Height:

0.220 inches

Mounting Surface To Terminal End Distance:

3.550 inches

Pole Quantity:

3

Mounting Facility Type And Quantity:

6 threaded hole

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

15.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

240.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

5000.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Magnetic all locations

Trip Release Characteristic:

Time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Internal Trip Release Configuration:

Series trip all locations

Thread Size:

0.138 inches

Trip Delay Time In Seconds Per Rated Continuous Current:

12.000 at 125 pct all locations and 80.000 at 125 pct all locations

Inclosure Protection Type For Which Designed:

Fungus resistant and moisture resistant

Frequency In Hertz:

50.0 all locations or 60.0 all locations

Thread Series Designator:

Unc

Terminal Type And Quantity:

6 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0